



REQUEST FOR PROPOSALS No. 19-002

One (1) New Landfill Crawler Excavator

Addendum No. 1

Issued: February 5, 2019

2 pages

Closing Date & Time: on or before 3:00 PM (15:00 hrs) PST on February 13, 2019

This addendum shall be read in conjunction with and considered as an integral part of the Request for Proposals. Revisions supersede the information contained in the original Proposal or previously issued Addendum. No consideration will be allowed for any extras due to any Proponent not being familiar with the contents of this Addendum. All other terms and conditions remain the same.

Questions & Answers

- Q1. I've noticed that the specification for track shoe width is 32 Inches Minimum on the tender. Our machine has a 31.5 inch track shoe, is that ok?
- A1. Delete: Track Width (Min. 32")
Replace with: Track Width (Min. 31")
- Q2. The tender states in section 4 that there be a thumb control (which there is) but in section 7 there is no thumb specified as an attachment.
- A2. Please add hydraulic thumb to the required attachments (section 7)
- Q3. Our machine has front wiper only, no rear wiper.
- A3. A rear wiper is not mandatory.
- Q4. There is bolt-on guarding available or 4-post cab-guard with catwalks. The 4-post cab-guard with catwalks requires substantially more cost of materials and labor to install. Can you specify which you would like?
- A4. The full 4 post cab guard with catwalks.

Q5. There is some other specific guarding available, if you would like to check out Accurate's webpage, it could help you narrow down the specifics. <https://www.accuratefabricating.com/excavator-products>

A5. Minimum requirements:

- ROPS- full cab/windshield guarding
- Catwalks
- Belly guards/ or stump guards some call them
- Rock guards on tracks
- All Hydraulic Cylinders guarded
- All moving hoses to be wrapped (steel), hard lined or guarded

Q6. Do you have a preference between a zero tail swing and full tail swing?

A6. Zero tail swing.

End of Addendum No. 1